

SEI GRAFFITI REMOVER GEL™

The SEI Graffiti Remover Gel utilizes SEI Technology™. This migratory chemistry fractures the molecular bonds in paints, lacquers, enamels, waxes and stains.

The SEI Graffiti Remover Gel migratory chemistry penetrates the graffiti and creates molecular space between the vandalism and the substrate, making the removal very easy.

The SEI Graffiti Remover Gel is VOC and Southern California Air

Quality Management District (AQMD) compliant and was designed for maximum consumer safety. This product does not contain any chlorinated solvents, methanol or acetone.

After the SEI Graffiti Remover Gel has penetrated the graffiti it can be easily removed by flushing with water. The removal time varies from 5 minutes to 1 hour, depending on the type of graffiti and amount to be removed.



Applications:

Can be used on:
Concrete, wood, stucco,
brick, stone, masonry, vinyl,
lexan, plastic, glass, metal,
and fiberglass.

Packaging:

Available in 5 or 55 gallon
containers.

Custom Packaging
Available.

Advantages:

VOC compliant
AQMD compliant
Environmentally friendly
Non-toxic
Low odor
Not regulated by the
Department of Transportation

See SEI Graffiti Remover Gel Product Data Sheet for further information

Method of Application:

The SEI Graffiti Remover Gel should be applied using a brush or roller. Sufficient time, between 5 minutes and 1 hour, should be allotted for the product to migrate and penetrate the vandalism. The graffiti should be washed away by flushing with water.