

SEI GRAFFITI REMOVER SPRAY™

The SEI Graffiti Remover Spray utilizes SEI Technology™. This migratory chemistry fractures the molecular bonds in paints, lacquers, enamels, waxes and stains.




The SEI Graffiti Remover Spray migratory chemistry penetrates the graffiti and creates molecular space between the vandalism and the substrate, making the removal very easy.

The SEI Graffiti Remover Spray is VOC and Southern California Air Quality Management District (AQMD) compliant and was designed for maximum consumer safety. This product does not

contain any chlorinated solvents, methanol or acetone.

Once the SEI Graffiti Remover Spray has penetrated the graffiti it can easily be removed by a flushing of water. The removal time varies from 45 seconds to 5 minutes, depending on the type of paint and amount of graffiti to be removed.

The SEI Graffiti Remover Spray is a multi-purpose environmental formulation and is effective on different types of paints, lacquers, enamels, waxes and marker.



Applications:

Can be used on: Concrete, wood, stucco, brick, stone, masonry, vinyl, lexan, plastic, glass, metal, and fiberglass.

Packaging:

12 oz. & 24 oz.
Aerosol or Trigger Spray Bottles.

Custom Sizes
Available.

Advantages:

VOC compliant

AQMD compliant

Environmentally friendly

Non-toxic

Low odor

Not regulated by the
Department of Transportation

Method of Application:

The SEI Graffiti Remover Spray should be applied using an airless sprayer, brush or roller. The SEI Graffiti Remover Spray should be applied over any graffiti or unwanted vandalism. Sufficient time, between 30 and 90 seconds, should be allowed for the product to migrate and penetrate the graffiti. After the SEI Graffiti Remover Spray has penetrated the graffiti, simply wash away with water.

See SEI Graffiti Remover Spray Product Data Sheet for further information

SEI™

ADVANCED CHEMICAL
TECHNOLOGY™