



SEI MASONRY RUST REMOVER[™]

AR-103

PRODUCT DESCRIPTION

The AR-103 is a biodegradable formulation that utilizes the CPT[®] corrosion inhibitor. The CPT chemistry will migrate through existing corrosion until it reaches the substrate. This creates molecular space between corrosion and substrate making corrosion removal very easy. This product does not contain muriatic or hydrochloric acids, which increase surface porosity, nor does it contain bleach, abrasives or caustic materials. Furthermore, it will not harm rubber, wood or plastic.

USE ON

Safe to remove rust from: Terrazzo, travertine, unglazed and unpolished stone, ceramics, brick, stucco, granite, limestone, terra cotta, concrete and other similar surfaces. It will not pit or etch these natural surfaces or grouting.

AR-103 will also remove atmospheric stains, chalking, efflorescence, mold and mildew without etching, pitting or damaging the surface.

TEST AREA

It is often impossible to know the conditions of the surface before cleaning. Before starting a project, it is important that a small test area be done on a hidden area. This product will harm aluminum, polished or painted surfaces.

APPLICATION

Apply cleaner liberally at full strength using a roller or plant sprayer. Allow product to remain on surface for approximately 2-7 minutes to penetrate the surface. Moderately agitate surface with brush, pad or automatic scrubbing equipment if need be. Let scrubber solution stand for another minute, then rinse surface with a pressure washer.

SHELF LIFE & STORAGE

Shelf life is approximately 6-8 months.

Heat reduces this shelf life, store in a cool place.

TECHNICAL DATA

- pH: 9.25-9.75
- lbs/gallon: 8.5-8.8
- Environmentally friendly
- User-safe
- Biodegradable
- VOC and AQMD compliant

DISCLAIMER:

The information provided is to be used as a guide and users should perform their own tests to ensure performance in their application. All data, statements, and recommendations made herein are based upon information we believe to be reliable, but are made without any representation, guarantee or warranty of accuracy. All statements, technical information and recommendations contained herein are based on tests SEI Chemical believes to be reliable, but the accuracy or completeness thereof is not guaranteed. SEI Chemical warrants SEI products will be free from defects when shipped to customer. SEI Chemical's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify SEI Chemical of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer. SEI Chemical shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of SEI Chemical. The foregoing warranty is exclusive and in lieu of all other warranties, express, implied or statutory, including without limitation any implied warranty of merchantability or of fitness for a particular purpose in no case shall SEI Chemical be liable for incidental or consequential damages. Limited warranty, for industrial use only. Keep out of reach of children, keep containers tightly closed, not for internal consumption, consult material. Consult Material Safety Data Sheet for more information.