

**SEI Chemical**

3430 Union Pacific Ave  
Los Angeles, CA 90023  
Tel: 323 263 4575 Fax: 888 273 4489

Product: **Form Release**

Product ID No.: **GCC-100FRO**

Emergency Phone #: Chemtel 800-255-3924

Material Safety Data Sheet

This Material Safety Data Sheet (MSDS) contains environmental, health and toxicology information for your employees. Please make sure this information is given to them. It also contains information to help you meet community Right To Know emergency response reporting requirements under SARA TITLE III and many other laws. If you resell this product, this MSDS must be given to the buyer or the information incorporated in your MSDS.

This MSDS complies with 29 CFR 1910.1200 (The Hazard Communication Standard)

**SECTION 1-PRODUCT DATA**

Chemical Name: Proprietary mixture of Release oil base stock

**SECTION II - HAZARDOUS INGREDIENTS**

CAS. Code:	Percent	TLV				Vapor Pressure
Ingredient	By weight	PPM	mg/m <sup>3</sup>	LEL%		mm Hg 20°C
(64742-54-7)						
Petroleum Oil Base Stock	90%	150 ppm	N.A	N.D		N.A.

WHIMIS Classification: Class B, Div 3, Class D, Div 2, SubDiv B

Product Class: Division 3

Not regulated under TDG by road or rail in packaging of 454L or less

Not regulated by DOT

**SECTION III - PHYSICAL DATA****SECTION IV - FIRE AND EXPLOSION Boiling Range: N.A.**

NFPA: Combustible Liquid

Vapor Pressure: N.D. Evaporation Rate: <1 (Butyl Acetate = 1)

Melting Range: N.A.

Specific Gravity: 0.88

Odour : Oil odor

Color: Light Brown

P.H.: N.A.

**HAZARD DATA**

Flash Point: 195°F TCC

Extinguishing Media Foam Carbon Dioxide Dry Chemical

Unusual Fire Explosion Hazards: N.A

Special Fire Fighting Procedures: Use precautions for oxidizing materials.

**SECTION V - REACTIVITY DATA**

Stability: Stable

Incompatibility (Materials To Avoid): Stray Oxidizing Agent

Hazardous Decomposition Products: None

Conditions To Avoid: Open flame

Avoid sources of open flames..

Hazardous Polymerization: Will Not Occur

NA - Not Applicable ND - Not Determined

**SECTION VI - HEALTH HAZARD DATA**

Emergency and First Aid Procedures: Eyes and Skin - Wash to remove chemical with soap and water.

Ingestion - Call a physician.

**SECTION VII - SPILL OR LEAK PROCEDURES**

Steps To Be Taken In Case Material Is Released or Spilled:

Remove material from sources of ignition or open flame.

In case of spill, sweep up and remove. Causes slippery condition when wet.

Waste Disposal Method: Dispose in accordance with local, state and federal regulations.

**SECTION VIII - SPECIAL PROTECTION INFORMATION**

Respiratory Protection: None - Mask if in enclosed areas.

Ventilation: Provide adequate exhaust ventilation to keep TLV below acceptable limits.

Protective Gloves: Optional

Eye Protection: Normal protection against foreign substances as needed-safety goggles.

**SECTION IX - SPECIAL PRECAUTIONS**

Precautions to Be Taken In Handling And Storing

1. Keep away from heat and open flame.

NA - Not Applicable ND - Not Determined

PREPARED BY: Craig Amen, Sr. Chemist

DATE PREPARED: 01/13/07 SUPERSEDES: 1/06/05

**Disclaimer:** This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of SEI Chemical. The data on this sheet relates only to the specific material designated herein. SEI Chemical assumes no legal responsibility for use or reliance upon these data.

The information provided is to be used as a guide and customers should perform their own tests to ensure performance in their application. All data, statements, and recommendations made herein are based upon information we believe to be reliable, but are made without any representation, guarantee or warranty of accuracy. All statements, technical information and recommendations contained herein are based on tests SEI Chemical believes to be reliable, but the accuracy or completeness thereof is not guaranteed. SEI Chemical warrants Corrosion Proof products will be free from defects when shipped to customer. SEI Chemical obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify SEI Chemical of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

SEI Chemical shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of SEI Chemical.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL SEI CHEMICAL BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.

LIMITED WARRANTY  
FOR INDUSTRIAL USE ONLY  
KEEP OUT OF REACH OF CHILDREN  
KEEP CONTAINER TIGHTLY CLOSED  
NOT FOR INTERNAL CONSUMPTION