

SEI Chemical
3137 E. 26th St
Vernon, CA 90058
Phone: 323 266 7111
Fax: 888 273 4489
Product: **SEI Corrosion Proof Oil Base**
Product ID No.: CPT-200
Material Safety Data Sheet

This Material Safety Data Sheet (MSDS) contains environmental, health and toxicology information for your employees. Please make sure this information is given to them. It also contains information to help you meet community Right To Know emergency response reporting requirements under SARA TITLE III and many other laws. If you resell this product, this MSDS must be given to the buyer or the information incorporated in your MSDS.

This MSDS complies with 29 CFR 1910.1200 (The Hazard Communication Standard)

Chemical Name: Proprietary mixture of Amine compound

Product Description: SEI Corrosion Proof Oil Base

Trade Name: SEI Corrosion Proof CPT-200

SECTION II - HAZARDOUS INGREDIENTS

CAS. Code: Ingredient (64742-88-7)	Percent By weight	PPM	TLV mg/m³	LEL%	Vapor Pressure mm Hg 20°C
Aliphatic Mineral Oil	45%	150 ppm	N.A	N.D	N.A.

SECTION III - PHYSICAL DATA

Color: Brown

Boiling Range: N.A. Form: Oil base Coating

Vapor Pressure: N.D Evaporation Rate: <1 (Butyl Acetate =1)

Odour : Solvent odor

Melting Range: N.A.

Specific Gravity: 0.88

P.H.: N.A.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Dot Category: UN No. 1300

Flash Point: 43°F TCC

LEL: 0.6

Extinguishing Media

Foam

Carbon Dioxide

Dry Chemical

Unusual Fire And Explosion Hazards

N.A

Special Fire Fighting Procedures

Use precautions for oxidizing materials.

SECTION V - REACTIVITY DATA

Stability: Stable

Incompatibility (Materials To Avoid): Stray Oxidizing Agent

Hazardous Decomposition Products: Oxides Of Sulfur

Conditions To Avoid: Product may support combustion.

Avoid sources of open flames, and hot equipment.

Hazardous Polymerization

Will Not Occur

Conditions To Avoid: Open Flame

NA - Not Applicable **ND** - Not Determined

SECTION VI - HEALTH HAZARD DATA

Threshold Limit Value: 150 ppm

Effects Of Overexposure

*May cause irritation to the mucous membrane.

*Repeated or prolonged skin contact with the chemical may produce mild skin irritation.

Emergency And First Aid Procedures

Eyes and Skin - Wash to remove chemical with soap and water.

Inhalation - Remove to fresh air

Ingestion - Call a physician.

SECTION VII - SPILL OR LEAK PROCEDURES

Steps To Be Taken In Case Material Is Released Or Spilled

Avoid prolonged inhalation of vapor.

Remove material from sources of ignition.

In case of spill, sweep up and remove. Causes slippery condition when wet.

Waste Disposal Method:

Dispose in accordance with local, state and federal regulations.

SECTION VIII - SPECIAL PROTECTION INFORMATION

Respiratory Protection:None

Ventilation: Provide adequate exhaust ventilation to keep TLV below acceptable limits.

Protective Gloves : Recommended use by not required

Eye Protection: Normal protection against foreign substances as needed-safety goggles.

Other Protective Equipment: None.

SECTION IX - SPECIAL PRECAUTIONS

Precautions To Be Taken In Handling And Storing

1. Keep away from heat and open flame.

Other Precautions

NIL

NA - Not Applicable ND - Not Determined

Disclaimer: This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of SEI Chemical. The data on this sheet relates only to the specific material designated herein. SEI Chemical assumes no legal responsibility for use or reliance upon these data. The information provided is to be used as a guide and customers should perform their own tests to ensure performance in their application. All data, statements, and recommendations made herein are based upon information we believe to be reliable, but are made without any representation, guarantee or warranty of accuracy. All statements, technical information and recommendations contained herein are based on tests SEI Chemical believes to be reliable, but the accuracy or completeness thereof is not guaranteed. SEI Chemical warrants Corrosion Proof products will be free from defects when shipped to customer. SEI Chemical obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify SEI Chemical of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer. SEI Chemical shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products. BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of SEI Chemical. THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL SEI CHEMICAL BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.

LIMITED WARRANTY

FOR INDUSTRIAL USE ONLY

KEEP OUT OF REACH OF CHILDREN

KEEP CONTAINER TIGHTLY CLOSED

NOT FOR INTERNAL CONSUMPTION

CONSULT MATERIAL SAFETY DATA SHEET FOR MORE INFORMATION