

SEI Chemical

19215 Parthenia St
Northridge, CA 91324
Phone: 818 998 3538
Fax: 818 998 5456

Product: **SEI Graffiti Remover – For SEI Graffiti Proofers**

Product ID No.: GR-SYS-P

Material Safety Data Sheet

Emergency #: Chemtel 800-255-3924

This Material Safety Data Sheet (MSDS) contains environmental, health and toxicology information for your employees. Please make sure this information is given to them. It also contains information to help you meet community Right To Know emergency response reporting requirements under SARA TITLE III and many other laws. If you resell this product, this MSDS must be given to the buyer or the information incorporated in your MSDS.

This MSDS complies with 29 CFR 1910.1200 (The Hazard Communication Standard)

SECTION I – PRODUCT IDENTIFICATION

PRODUCT DESCRIPTION: SEI Graffiti Remover Spray P

D.O.T. PROPER SHIPPING NAME: ORM-D Consumer Commodity

NFPA CODES: HEALTH – 2 FLAMMABILITY – 3 CORROSIVE – 0 REACTIVITY – 0

SECTION II – COMPONENTS

ACETONE

CAS #: 67-64-1

PEL: TWA 1000 PPM

TLV: TWA 750 PPM STEL 1000PPM

CARBON DIOXIDE COMPRESSED GAS

CAS #: 124-38-9 PEL: 5000 MOLAR PPM

TLV: 30000 MOLAR PPM

PROPRIATERY

*** If present, IARC, NTP and OSHA carcinogens and chemical subject to this reporting requirements of SARA TITLE III, SECTION 313 are identified in this section.

SECTION III – PHYSICAL DATA

BOILING POINT FOR PRODUCT: 133°F

VAPOR PRESSURE FOR PRODUCT: 185 mmHg

VAPOR DENSITY FOR PRODUCT: (Air=1): 2.0

SPECIFIC GRAVITY: 0.78@60°F

V.O.C.: (Grams per Litre): <25

WATER SOLUBILITY: >0.80%

APPEARANCE: Clear Liquid

C.A.R.B. & SCAQMD: COMPLIANT

SECTION IV – FIRE AND EXPLOSION DATA

FLASH POINT (CC): 4 F.

EXPLOSIVE LIMIT (PRODUCT): Lower – 1.1

UPPER – 7.5

GENERAL HAZARD:

FIRE FIGHTING: Use foam, dry chemical, or water spray to extinguish fire.

SECTION V – HEALTH HAZARD DATA

SECTION 05.20

EYE CONTACT: Flush eyes with large quantities of water for at least 15 minutes. Consult a physician.

SKIN CONTACT: Wash with soap and water

INHALATION: Remove to fresh air.

INGESTION: Give water but do not induce vomiting. Get medical attention.

SECTION VI – REACTIVITY DATA

SECTION 06.20

STABILITY: Stable.

CONDITIONS TO AVOID: Contact with incompatible materials.

HAZARDOUS POLYMERIZATION: Will not occur.

MATERIALS AND CONDITIONS TO AVOID INCOMPATIBILITY: Strong oxidizers, acids, peroxides and halogens.

SECTION VII – SPILL OR LEAK PROCEDURES

SECTION 07.20

SMALL SPILL: Absorb on sweeping compound or other absorbent material.

LARGE SPILL: Eliminate all sources of ignition. All persons not wearing protective equipment should be excluded from the area of spill until clean up has been completed. Stop spill at source, dike area of spill to prevent spreading, pump liquid to salvage tank. Remove remaining liquid on sand, clay, earth, floor absorbent, or other absorbent material and place in containers. Notify proper authorities as required by local, state and federal regulations.

SECTION VIII – PROTECTIVE EQUIPMENT TO BE USED

SECTION 08.20

RESPIRATORY PROTECTION: None

EYES: Safety glasses/splash goggles

GLOVES: Recommended

SECTION IX – SPECIAL PRECAUTIONS OR OTHER COMMENTS

SECTION 09.20

HANDLING AND STORAGE PRECAUTIONS: Keep containers tightly closed. Completely drain "empty" drums; properly dispose in an environmentally safe manner and in accordance with governmental regulations. Recycle drums only through qualified reprocessing organizations.

PREPARED BY: Craig Amen, Sr. Chemist

APPROVED BY: Roland Fransisco, CTO

DATE PREPARED: 02/26/06 SUPERSEDES: 11/21/05

ADDITIONAL COMMENTS

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest

modification of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.