

SEI Chemical
PRODUCT DATA SHEET
SEI GRAFFITI REMOVER GEL

Product Description:

The SEI Graffiti Remover Gel utilizes the SEI Migratory Technology that penetrates and chemically fractures the molecular bonds in paints, lacquers, enamels and stains. The SEI Graffiti Remover Gels active ingredient migrates and penetrates paints, coatings or unwanted marks and creates molecular space between the vandalism and the substrate, making the removal easy. The formula was designed for maximum consumer safety and therefore does not contain methylene chloride, chlorinated solvents, methanol, toluene, acetone, etc. All SEI Graffiti Removers have a unique combination of vapor and contact inhibiting abilities to prevent corrosion, flash rusting and discoloration of stainless steel, iron, copper, aluminum and brass after paint removal.

This Gel formulation creates a loose end substance that can be removed by a flushing of water or by the use of a brush or rag. The stripping time varies from three minutes and sixty minutes, depending on the type of coating and number of coatings to be removed.

The SEI Graffiti Remover Gel was formulated as a thixotropic gel for special applications that require the chemical to cling to vertical, horizontal or surfaces of complex geometry. The SEI Graffiti Remover Gel is a multi-purpose formulation and is effective on different types of paints, coatings, lacquers, enamels, waxes, etc.

Typical Uses:

Any porous material: Concrete, wood, stucco, brick, stone, masonry, vinyl, canvas, etc.

SEI Chemical
PRODUCT DATA SHEET
SEI GRAFFITI REMOVER GEL

Chief Advantages:

- Not regulated by the Department of Transportation.
- Relatively low odor.
- Exempt from Rule 422 (photochemically non-reactive)
- Non-corrosive.
- Can be stored indoors without restrictions.
- Exempt from Rule 1171 - AQMD

Packaging:

- 5, 55 - gal Container.
- Any size custom packaging available

Method of Application:

The SEI Graffiti Remover Gel should be applied in full strength. Under ambient conditions, the use of a brush or warm water spray is recommended. Sufficient time (between three and sixty minutes) should be allowed for the product to migrate and penetrate the vandalism. Loose substrate may be scraped or washed away with water. If sanding and refinishing is used, the surface should be allowed to dry. If desired

The SEI Graffiti Remover Gel may be applied in full strength using an airless sprayer.

***NOTE:** This product must be shaken or stirred before use.